This Page Is Inserted by IFW Operations and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents will not correct images, please do not report the images to the Image Problem Mailbox.

P. JENT COOPERATION TREAT

To:

From the	INTERNA	ATIONAL	BUREAU
----------	---------	---------	--------

PCT

NOTIFICATION OF ELECTION

(PCT Rule 61.2)

United States Patent and Trademark Office (Box PCT)

Crystal Plaza 2 Washington, DC 20231 ÉTATS-UNIS D'AMÉRIQUE

Date of mailing (day/month/year)
23 June 1999 (23.06.99)

International application No.
PCT/EP98/07215

International filing date (day/month/year)
09 November 1998 (09.11.98)

Applicant

CROZIER, Hérve et al

X in the demand filed with the International Preliminary Examining Authority on:
20 May 1999 (20.05.99)
in a notice effecting later election filed with the International Bureau on:
The election X was
was not
made before the expiration of 19 months from the priority date or, where Rule 32 applies, within the time limit under Rule 32.2(b).

The International Bureau of WIPO 34, chemin des Colombettes 1211 Geneva 20, Switzerland

Authorized officer

Jean-Marie McAdams

Facsimile No.: (41-22) 740.14.35 Telephone No.: (41-22) 338.83.38



From the INTERNATIONAL PRELIMINARY EXAMINING AUTHORITY

To:

LAINE, Seppo SEPPO LAINE OY Itämerenkatu 3b FI-00180 Helsinki FINLANDE

PCT

NOTIFICATION OF TRANSMITTAL OF THE INTERNATIONAL PRELIMINARY EXAMINATION REPORT (PCT Rule 71.1)

Date of mailing (day/month/year)

0 8. 02. 00

Applicant's or agent's file reference

BOR 10 PCT

PCT/EP98/07215

International filing date (day/month/year)

09/11/1998

Priority date (day/month/year)

IMPORTANT NOTIFICATION

07/11/1997

Applicant

BOREALIS A/S et al.

International application No.

- 1. The applicant is hereby notified that this International Preliminary Examining Authority transmits herewith the international preliminary examination report and its annexes, if any, established on the international application.
- 2. A copy of the report and its annexes, if any, is being transmitted to the International Bureau for communication to all the elected Offices.
- 3. Where required by any of the elected Offices, the International Bureau will prepare an English translation of the report (but not of any annexes) and will transmit such translation to those Offices.

4. REMINDER

The applicant must enter the national phase before each elected Office by performing certain acts (filing translations and paying national fees) within 30 months from the priority date (or later in some Offices) (Article 39(1)) (see also the reminder sent by the International Bureau with Form PCT/IB/301).

Where a translation of the international application must be furnished to an elected Office, that translation must contain a translation of any annexes to the international preliminary examination report. It is the applicant's responsibility to prepare and furnish such translation directly to each elected Office concerned.

For further details on the applicable time limits and requirements of the elected Offices, see Volume II of the PCT Applicant's Guide.

Name and mailing address of the IPEA/

Authorized officer

European Patent Office D-80298 Munich

Connolly, M

Tel. +49 89 2399 - 0 Tx: 523656 epmu d Fax: +49 89 2399 - 4465

Tel.+49 89 2399-8021



INTERNATIONAL PRELIMINARY . EXAMINATION REPORT

International application No. PCT/EP98/07215

I.	Bas	is (of t	he	r	port
----	-----	------	------	----	---	------

1. This report has been drawn on the basis of (substitute sheets which have been furnished to the receiving Office in

•	resp	esponse to an invitation under Article 14 are referred to in this report as "originally filed" and are not annexed the report since they do not contain amendments.):							l to
	Des	cription, pages:							
	1,2, 14-1	4,5,7-12, 19	as originally f	filed					
	3,6,	13	as received o	on	03/	/12/1999	with letter of	03/12/1999	
	Clai	ims, No.:							
	1-13	3	as received o	on	03/	/12/1999	with letter of	03/12/1999	
2.	The	amendments have	e resulted in th	ne cancell	lation of:				
		the description,	pages:						
		the claims,	Nos.:						
		the drawings,	sheets:						
3.	×	This report has be considered to go	een establishe beyond the dis	d as if (so sclosure a	ome of) the a as filed (Rule	amendmen 70.2(c)):	ts had not been r	made, since they have b	een
		see separate she	eet						
4.	Add	litional observation	ns, if necessar	y:					
								·	
								•	
۷.	Rea app	asoned statement olicability; citation	under Article s and explan	e 35(2) w nations si	ith regard to upporting so	o novelty, uch stater	inventive step o nent	or industrial	
1.	Sta	tement							
	Nov	velty (N)	Yes: No:	Claims Claims	1-13				
	Inv	entive step (IS)	Yes: No:	Claims Claims	1-13				•
	Ind	ustrial applicability	(IA) Yes: No:	Claims Claims	1-13				

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

International application No. PCT/EP98/07215

2. Citations and explanations

see separate sheet

VIII. Certain observations on the international application

The following observations on the clarity of the claims, description, and drawings or on the question whether the claims are fully supported by the description, are made:

see separate sheet

EXAMINATION REPORT - SEPARATE SHEET

Re Item I

Basis of the report

The applicant has not indicated the passage(s) of the application as filed on which the amendments to operative Claims 3 and 11 are based.

These amendments are considered to contravene Art. 34(2)(b) PCT.

Re Item V

Reasoned statement under Rule 66.2(a)(ii) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement

Reference is made to the following documents:

D1: EP-A-0 152 701 (cited in the application)

D2: EP-A-0 151 883 D3: GB-A-1 104 665

The claimed subject-matter differs from the teaching of D1 - D3 in that the concentration of the colour pigment is defined.

The prior art documents on file are silent on shrinkage problems associated with pigment-containing propylene polymer compositions.

Therefore, the subject-matter of Claims 1-13 is regarded to meet the requirements of Art. 33 (2)-(4) PCT.

Re Item VIII

Certain observations on the international application

Claims 3 and 11 are unclear since the conditions under which the shrinkage occurs are not defined (Art. 6 PCT).

Reference is made in this respect to the last par. at p. 13, which refers to a variation in shrinkage in both flow and cross direction of less than 5 % for white, red and blue pigments (compared to conventional, non-nucleated polymers).

3

The use of vinyl compounds, such as polymers of vinyl cycloalkanes and 3-methyl-1-butene, as nucleating agents in the form of reactor made blends of polypropylene and polymerised vinyl compounds or polypropylene compounds, is suggested in the prior art, cf. EP Patent Specifications Nos. 0 152 701, 0 151 883, 0 368 577 and 0 417 319.

However, none of the prior art publications makes any reference to the use of these highly nucleated materials for the production of coloured caps and closures.

5

10

15

25

30

According to the present invention it has now surprisingly been found that propylene homo- or copolymers nucleated with a component containing polymerized vinyl compound units will give excellent dimensional consistency by dominating the pigments' nucleating effect with its strong nucleation. The strongly nucleating effect of the polymeric nucleating agent is apparent from the high crystallisation temperature of the polymer. Thus, the crystallisation temperature of the material is at least 7 °C, preferably 10 °C and in particular over 13 °C higher than the crystallisation temperature of the corresponding non-nucleated polymer and the material exhibits a fast crystallisation rate. Caps of various colours moulded with a polypropylene nucleated with a polymerised vinyl compound grade to provide a composition according to the present invention will therefore have practically the same dimensions.

More specifically, the polymer composition according to the present invention is characterized by what is stated in the characterizing part of claim 1.

The process according to the present invention for preparing coloured polypropylene compositions is characterized by what is stated in the characterizing part of claim 10.

The present compositions can be used in any kind of polymer articles. Particular advantages are obtained by applying the compositions to the manufacture of injection moulded and/or compression moulded products as well as articles produced by thermoforming, blow moulding and film and sheet extrusion.

The invention achieves a number of considerable advantages. In particular it should be pointed out that the strong nucleating effect of a polymeric nucleating agent containing

AMENDED SHEET

wherein R_1 and R_2 together form a 5 or 6 membered saturated or unsaturated or aromatic ring or they stand independently for a lower alkyl comprising 1 to 4 carbon atoms.

......

The following specific examples of vinyl compounds can be mentioned: vinyl cycloalkanes, in particular vinyl cyclohexane, vinyl cyclopentane, vinyl-2-methyl cyclohexane and vinyl norbornane, 3-methyl-1-butene, styrene, p-methyl-styrene, 3-ethyl-1-hexene or mixtures thereof. Vinyl cyclohexane (VCH) is a particularly preferred monomer but, for example, 3-methyl-1-butene can be used as a monomer or comonomer to adjust the crystallisation temperature.

10

15

5

For the purpose of the present invention "nucleated propylene polymer" stands for a polymer having an increased and controlled degree of crystallinity preferably amounting to over 50 % and preferably having a crystallization temperature of more than 7 °C, preferably over 10 °C and in particular over 13 °C of the T_{cr} of the corresponding non-nucleated polymer. Using MgCl₂-supported high-yield Ziegler-Natta catalysts crystallization temperatures of more than 120 °C, preferably over 124 °C and in particular over 126 °C can be obtained. In compositions containing colouring pigments having a nucleating effect, particularly advantageous results are obtained by using polymers having a crystallization temperature over 15 °C higher than that of the corresponding non-nucleated polymer (for a polymer produced with the above-mentioned ZN-catalyst, 128 °C).

25

30

20

According to a preferred embodiment of the present invention, modification of the catalyst by polymerizing a vinyl compound, such as VCH, in the presence thereof is performed in an inert fluid which does not dissolve the polymer formed (e.g. polyVCH). One particularly preferred polymerization medium comprises a viscous substance, in the following a "wax", such as an oil or a mixture of an oil with a solid or semi-solid polymer (oil-grease). The viscosity of such a viscous substance is usually 1,000 to 15,000 cP (1 - 15 Ns/m²) at room temperature. The advantage of wax prepolymerization is that the catalyst can be prepolymerized, stored and fed into the process in the same media and catalyst wax preparation and prepolymerization is performed in the same process device. Due to the fact that no washing, drying, sieving and transferring thus are needed, the catalyst activity

high-yield Ziegler-Natta catalysts, having high stiffness, an increased overall degree of crystallization and a crystallization temperature of the propylene homopolymer fraction of more than 120 °C, preferably over 124 °C and in particular over 126 °C. The degree of crystallization for a propylene homopolymer is generally over 48 %, and often over 50 %.

5

15

30

The amount of the nucleating polymeric agent is, in case of propylene polymers or copolymers, about 0.0001 to 1 wt-%, and in case of polypropylene blends about 0.0001 to 0.5 wt-%.

This nucleated polypropylene (100 parts by weight) is blended with 0.01 to 5 parts by weight of the coloured pigment of choise. The particle size of the pigment is usually 0.01 to 1000 micrometre and more often 0.1 to 10 micrometre.

The colouring agent is usually in the form of a masterbatch comprising also a polymer carrier. The blending with the polypropylene is directly done at the conversion machine (e.g. extruder, injection moulding machine...) by dosing the pigment with a gravimetric side feeder. When the colouring agent is liquid it is dosed with a liquid pump.

The present polymers and copolymers of propylene can be blended and optionally compounded with additives and adjuvants conventionally used in the art. Thus, suitable additives include antistatic agents, flame retardants, light and heat stabilizers, reinforcement agents, pigments and carbon black. Fillers such as mica, CaCO₃, talc and wollastonite can also be used. Further, the polymers and copolymers can be blended with non-nucleated propylene and/or with other polymers, in particular other polyolefins, such as LD-, LLD-, MD- and HD-polyethylenes and polybutylene.

Compositions according to the invention containing pigments will exhibit very small variation in shrinkage irrespective of the colouring agent used. As the results indicated below in Table 1 show, the variation in shrinkage in both flow and cross direction is less than 5 % for white, red and blue pigments compared to conventional, non-nucleated polymers having a variation of shrinkage in the range of 10 to 20 %. The fact that the pigments' nucleating effect is clearly dominated by the nucleated polypropylene with its

5

15

20

25

30

1. Coloured polymer composition comprising

- a propylene polymer nucleated with a polymerized vinyl compound and having an at least 7 °C higher crystallization temperature than that of the corresponding nonnucleated polymer, and
- a colour pigment having a concentration of 0.01 to 5 wt-% calculated from the weight of the nucleated propylene polymer.
- 2. The composition according to claim 1, wherein the colour pigment has a nucleating effect on the propylene polymer.
 - 3. The composition of claim 1 or 2, wherein the shrinkage of the composition, calculated by comparing the measured dimension of an injection moulded box with the nominal mould dimension, varies less than 5 % for different colour pigments.
 - 4. The polymer composition according to claim 1, wherein the propylene polymer contains about 0.0001 to 1 % by weight of units derived from a vinyl compound of the formula

R

wherein R₁ and R₂ together form a 5 or 6 membered saturated or unsaturated or aromatic ring or they stand independently for a lower alkyl comprising 1 to 4 carbon atoms.

- 5. The polymer composition according to claim 4, wherein the propylene polymer contains cycloalkane units, in particular vinyl cyclohexane, vinyl cyclopentane, vinyl-2-methyl cyclohexane and vinyl norbomane, 3-methyl-1-butene, styrene, p-methyl-styrene or 3-ethyl-hexene units or mixtures thereof.
- 6. The polymer composition according to any of claims 1 to 5, wherein the nucleated

AMENDED SHEET



propylene polymer comprises a propylene polymer copolymer polymerized in the presence of a catalyst modified with a polymer containing vinyl compound units.

7. The polymer composition according to any of claims 1 to 5, wherein the nucleated propylene polymer comprises a propylene homo- or copolymer blended with a polymer containing polymerised vinyl compound units.

5

10

15

20

25

30

١

- 8. The polymer composition according to any of the preceding claims, wherein the pigment is selected from the group of white pigments, yellow/orange pigments, red/violet pigments, blue/green pigments and carbon black.
- 9. The polymer composition according to claim 8, wherein the pigment is selected from the group of titanium dioxide, isoindolinone, azocondensation, quinacridone, diketo pyrrole pyrrol, ultramarine blue, Cu Phtalocyanine blue and carbon black.
- 10. A process for preparing a coloured polymer composition comprising a propylene polymer and a colour pigment, characterized by using a propylene polymer nucleated with a polymerized vinyl compound and having an at least 7 °C higher crystallization temperature than the corresponding non-nucleated polymer, the concentration of the colouring pigment being 0.01 to 5 wt-% calculated from the weight of the nucleated propylene polymer,.
- 11. The process according to claim 10 wherein 100 parts by weight of a nucleated polypropylene composition containing about 0.0001 to 1 % by weight of units derived from a vinyl compound of the formula

$$R_2$$

wherein R₁ and R₂ together form a 5 or 6 membered saturated or unsaturated or aromatic

ring or they stand independently for a lower alkyl comprising 1 to 4 carbon atoms is blended with 0.01 to 5 parts by weight of a colouring pigment selected from the group of white pigments, green pigments, red pigments, blue pigments and carbon black, to provide a coloured polypropylene composition, the shrinkage of which varies less than 5 % for different colour pigments, said shrinkage being calculated by comparing the measured dimension of an injection moulded box with the nominal mould dimension.

5

10

- 12. Use of a polymer composition according to any of claims 1 to 9 for the manufacture of polymer articles by injection moulding or compression moulding, thermoforming, blow moulding, film or sheet extrusion, pipe or cable extrusion.
- 13. The use of claim 12, wherein caps and closures for food, household, hygiene and health-care applications are manufactured.



PCT



INTERNATIONAL SEARCH REPORT

(PCT Article 18 and Rules 43 and 44)

Applicant's or agent's file reference BOR 10 PCT		of Transmittal of International Search Report 20) as well as, where applicable, item 5 below.					
International application No.	International filing date (day/month/year)	(Earliest) Priority Date (day/month/year)					
PCT/EP 98/07215 09/11/1998 07/11/1997							
BOREALIS A/S et al.	,						
according to Article 18. A copy is being tra This International Search Report consists	_						
1. Basis of the report							
	international search was carried out on the bases otherwise indicated under this item.	sis of the international application in the					
the international search w Authority (Rule 23.1(b)).	as carried out on the basis of a translation of t	he international application furnished to this					
was carried out on the basis of the		nternational application, the international search					
filed together with the inte	rnational application in computer readable for	n.					
furnished subsequently to	this Authority in written form.						
furnished subsequently to	this Authority in computer readble form.						
	osequently furnished written sequence listing d s filed has been furnished.	oes not go beyond the disclosure in the					
the statement that the info furnished	ormation recorded in computer readable form is	s identical to the written sequence listing has been					
2. Certain claims were fou	nd unsearchable (See Box I).						
3. Unity of invention is lac	king (see Box II).						
4. With regard to the title,							
the text is approved as su	bmitted by the applicant.						
the text has been established by this Authority to read as follows:							
5. With regard to the abstract,							
the text is approved as su	· · · · · · · · · · · · · · · · · · ·	h, so it sappare in Poy III. The sapplicant man					
	hed, according to Rule 38.2(b), by this Authori e date of mailing of this international search rep						
6. The figure of the drawings to be public	ished with the abstract is Figure No.						
as suggested by the appl	icant.	None of the figures.					
because the applicant fail	ed to suggest a figure.						
because this figure better characterizes the invention.							

A. CLASSIFICATION OF SUBJECT MATTER IPC 6 C08K5/00 C08L23/10

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 CO8K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT							
Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.					
A	EP 0 369 658 A (SUMITOMO) 23 May 1990 see page 2, line 40 - line 45; claims 1-3; examples; table 1	1,4,5					
Α	EP 0 417 319 A (MITSUBISHI) 20 March 1991 cited in the application see page 2, line 24 - line 35; claims 1,5; examples	1,4-7					
Α	GB 1 104 665 A (ICI LTD.) see page 1, line 19 - line 20 see page 1, line 39 - line 53 see page 1, line 65 - line 70 see page 2, line 24 - line 26 see page 3, line 52 - line 61; claims 1,4,5,11,13,19,34; examples -/	1,4-6,13					

Further documents are listed in the continuation of box C.	Patent family members are listed in annex.			
 Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the international filling date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filling date but later than the priority date claimed 	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention. "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone. "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art. "&" document member of the same patent family			
Date of the actual completion of the international search	Date of mailing of the international search report			
20 April 1999	03/05/1999			
Name and mailing address of the ISA	Authorized officer			
European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016	Engel, S			

1

INTER IONAL SEARCH REPORT

Internal Application No
PCT/EP 98/07215


Jation) DOCUMENTS CONSIDERED TO BE RELEVANT	TB to the second
Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
EP 0 151 883 A (SUMITOMO) 21 August 1985 cited in the application see page 15, line 23 - page 16, line 2; claims 1,6-9; examples; table 2	1,4-6
·	
·	

INTERMITIONAL SEARCH REPORT

Information on patent family members

Int ponal Application No
PCT/EP 98/07215

Patent document cited in search repor	t	Publication date	1	Patent family member(s)	Publication date
EP 369658	А	23-05-1990	JP JP CA DE DE SG US	2135245 A 2762492 B 2001234 A,C 68928768 D 68928768 T 47424 A 5032645 A 5115027 A	24-05-1990 04-06-1998 16-05-1990 10-09-1998 14-01-1999 17-04-1998 16-07-1991 19-05-1992
EP 417319	A	20-03-1991	JP JP JP DE DE US WO	2793871 B 3028246 A 3014852 A 69028752 D 69028752 T 5286540 A 9011328 A	03-09-1998 06-02-1991 23-01-1991 07-11-1996 06-03-1997 15-02-1994 04-10-1991
GB 1104665	Α		BE DE FR NL	679547 A 1595842 A 1476249 A 6605058 A	14-10-1966 14-05-1970 21-06-1967 17-10-1966
EP 151883	Α	21-08-1985	JP JP CA CA DE EP SG US	1761591 C 3042298 B 60139731 A 1255048 A 1254690 A 3471942 A 0152701 A 96994 G 4696979 A 4551501 A	28-05-1993 26-06-1991 24-07-1985 30-05-1989 23-05-1989 14-07-1988 28-08-1985 12-05-1995 29-09-1987 05-11-1985



5

10

15

The use of vinyl compounds, such as polymers of vinyl cycloalkanes and 3-methyl-1-butene, as nucleating agents in the form of reactor made blends of polypropylene and polymerised vinyl compounds or polypropylene compounds, is suggested in the prior art, cf. EP Patent Specifications Nos. 0 152 701, 0 151 883, 0 368 577 and 0 417 319.

However, none of the prior art publications makes any reference to the use of these highly nucleated materials for the production of coloured caps and closures.

According to the present invention it has now surprisingly been found that propylene homo- or copolymers nucleated with a component containing polymerized vinyl compound units will give excellent dimensional consistency by dominating the pigments' nucleating effect with its strong nucleation. The strongly nucleating effect of the polymeric nucleating agent is apparent from the high crystallisation temperature of the polymer. Thus, the crystallisation temperature of the material is at least 7 °C, preferably 10 °C and in particular over 13 °C higher than the crystallisation temperature of the corresponding non-nucleated polymer and the material exhibits a fast crystallisation rate. Caps of various colours moulded with a polypropylene nucleated with a polymerised vinyl compound grade to provide a composition according to the present invention will therefore have practically the same dimensions.

More specifically, the polymer composition according to the present invention is characterized by what is stated in the characterizing part of claim 1.

The process according to the present invention for preparing coloured polypropylene compositions is characterized by what is stated in the characterizing part of claim 10.

The present compositions can be used in any kind of polymer articles. Particular advantages are obtained by applying the compositions to the manufacture of injection moulded and/or compression moulded products as well as articles produced by thermoforming, blow moulding and film and sheet extrusion.

The invention achieves a number of considerable advantages. In particular it should be pointed out that the strong nucleating effect of a polymeric nucleating agent containing

30

25

wherein R₁ and R₂ together form a 5 or 6 membered saturated or unsaturated or aromatic ring or they stand independently for a lower alkyl comprising 1 to 4 carbon atoms.

The following specific examples of vinyl compounds can be mentioned: vinyl cycloalkanes, in particular vinyl cyclohexane, vinyl cyclopentane, vinyl-2-methyl cyclohexane and vinyl norbornane, 3-methyl-1-butene, styrene, p-methyl-styrene, 3-ethyl-1-hexene or mixtures thereof. Vinyl cyclohexane (VCH) is a particularly preferred monomer but, for example, 3-methyl-1-butene can be used as a monomer or comonomer to adjust the crystallisation temperature.

For the purpose of the present invention "nucleated propylene polymer" stands for a polymer having an increased and controlled degree of crystallinity preferably amounting to over 50 % and preferably having a crystallization temperature of more than 7 °C, preferably over 10 °C and in particular over 13 °C of the T_{cr} of the corresponding non-nucleated polymer. Using MgCl₂-supported high-yield Ziegler-Natta catalysts crystallization temperatures of more than 120 °C, preferably over 124 °C and in particular over 126 °C can be obtained. In compositions containing colouring pigments having a nucleating effect, particularly advantageous results are obtained by using polymers having a crystallization temperature over 15 °C higher than that of the corresponding non-nucleated polymer (for a polymer produced with the above-mentioned ZN-catalyst, 128 °C).

According to a preferred embodiment of the present invention, modification of the catalyst by polymerizing a vinyl compound, such as VCH, in the presence thereof is performed in an inert fluid which does not dissolve the polymer formed (e.g. polyVCH). One particularly preferred polymerization medium comprises a viscous substance, in the following a "wax", such as an oil or a mixture of an oil with a solid or semi-solid polymer (oil-grease). The viscosity of such a viscous substance is usually 1,000 to 15,000 cP (1 - 15 Ns/m²) at room temperature. The advantage of wax prepolymerization is that the catalyst can be prepolymerized, stored and fed into the process in the same media and catalyst wax preparation and prepolymerization is performed in the same process device. Due to the fact that no washing, drying, sieving and transferring thus are needed, the catalyst activity

high-yield Ziegler-Natta catalysts, having high stiffness, an increased overall degree of crystallization and a crystallization temperature of the propylene homopolymer fraction of more than 120 °C, preferably over 124 °C and in particular over 126 °C. The degree of crystallization for a propylene homopolymer is generally over 48 %, and often over 50 %.

5

The amount of the nucleating polymeric agent is, in case of propylene polymers or copolymers, about 0.0001 to 1 wt-%, and in case of polypropylene blends about 0.0001 to 0.5 wt-%.

10

This nucleated polypropylene (100 parts by weight) is blended with 0.01 to 5 parts by weight of the coloured pigment of choise. The particle size of the pigment is usually 0.01 to 1000 micrometre and more often 0.1 to 10 micrometre.

15

The colouring agent is usually in the form of a masterbatch comprising also a polymer carrier. The blending with the polypropylene is directly done at the conversion machine (e.g. extruder, injection moulding machine...) by dosing the pigment with a gravimetric side feeder. When the colouring agent is liquid it is dosed with a liquid pump.

20

The present polymers and copolymers of propylene can be blended and optionally compounded with additives and adjuvants conventionally used in the art. Thus, suitable additives include antistatic agents, flame retardants, light and heat stabilizers, reinforcement agents, pigments and carbon black. Fillers such as mica, CaCO₃, talc and wollastonite can also be used. Further, the polymers and copolymers can be blended with non-nucleated propylene and/or with other polymers, in particular other polyolefins, such as LD-, LLD-, MD- and HD-polyethylenes and polybutylene.

25

30

Compositions according to the invention containing pigments will exhibit very small variation in shrinkage irrespective of the colouring agent used. As the results indicated below in Table 1 show, the variation in shrinkage in both flow and cross direction is less than 5 % for white, red and blue pigments compared to conventional, non-nucleated polymers having a variation of shrinkage in the range of 10 to 20 %. The fact that the pigments' nucleating effect is clearly dominated by the nucleated polypropylene with its

IN THE CLAIMS:

- 1. Coloured polymer composition comprising
 - a propylene polymer nucleated with a polymerized vinyl compound and having an at least 7 °C higher crystallization temperature than that of the corresponding nonnucleated polymer, and
 - a colour pigment having a concentration of 0.01 to 5 wt-% calculated from the weight of the nucleated propylene polymer.
- 2. The composition according to claim 1, wherein the colour pigment has a nucleating effect on the propylene polymer.
 - 3. The composition of claim 1 or 2, wherein the shrinkage of the composition, calculated by comparing the measured dimension of an injection moulded box with the nominal mould dimension, varies less than 5 % for different colour pigments.
 - 4. The polymer composition according to claim 1, wherein the propylene polymer contains about 0.0001 to 1 % by weight of units derived from a vinyl compound of the formula

20

25

30

15

5

$$R_2$$

wherein R_1 and R_2 together form a 5 or 6 membered saturated or unsaturated or aromatic ring or they stand independently for a lower alkyl comprising 1 to 4 carbon atoms.

- 5. The polymer composition according to claim 4, wherein the propylene polymer contains cycloalkane units, in particular vinyl cyclohexane, vinyl cyclopentane, vinyl-2-methyl cyclohexane and vinyl norbornane, 3-methyl-1-butene, styrene, p-methyl-styrene or 3-ethyl-hexene units or mixtures thereof.
- 6. The polymer composition according to any of claims 1 to 5, wherein the nucleated

propylene polymer comprises a propylene polymer copolymer polymerized in the presence of a catalyst modified with a polymer containing vinyl compound units.

- 7. The polymer composition according to any of claims 1 to 5, wherein the nucleated propylene polymer comprises a propylene homo- or copolymer blended with a polymer containing polymerised vinyl compound units.
 - 8. The polymer composition according to any of the preceding claims, wherein the pigment is selected from the group of white pigments, yellow/orange pigments, red/violet pigments, blue/green pigments and carbon black.
 - 9. The polymer composition according to claim 8, wherein the pigment is selected from the group of titanium dioxide, isoindolinone, azocondensation, quinacridone, diketo pyrrolo pyrol, ultramarine blue, Cu Phtalocyanine blue and carbon black.

10. A process for preparing a coloured polymer composition comprising a propylene polymer and a colour pigment, characterized by using a propylene polymer nucleated with a polymerized vinyl compound and having an at least 7 °C higher crystallization temperature than the corresponding non-nucleated polymer, the concentration of the colouring pigment being 0.01 to 5 wt-% calculated from the weight of the nucleated propylene polymer,.

11. The process according to claim 10 wherein 100 parts by weight of a nucleated polypropylene composition containing about 0.0001 to 1 % by weight of units derived from a vinyl compound of the formula

30

25

5

10

15

20

ring or they stand independently for a lower alkyl comprising 1 to 4 carbon atoms is blended with 0.01 to 5 parts by weight of a colouring pigment selected from the group of white pigments, green pigments, red pigments, blue pigments and carbon black, to provide a coloured polypropylene composition, the shrinkage of which varies less than 5 % for different colour pigments, said shrinkage being calculated by comparing the measured dimension of an injection moulded box with the nominal mould dimension.

5

10

- 12. Use of a polymer composition according to any of claims 1 to 9 for the manufacture of polymer articles by injection moulding or compression moulding, thermoforming, blow moulding, film or sheet extrusion, pipe or cable extrusion.
- 13. The use of claim 12, wherein caps and closures for food, household, hygiene and health-care applications are manufactured.

PCT

rec'd		FEB 2000	
WIPC)	PCT	

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

(PCT Article 36 and Rule 70)

Applicant's	or ager	it's file reference		See Notif	ication of Transmittal of International	
BOR 10 F	РСТ		FOR FURTHER ACTION		ry Examination Report (Form PCT/IPEA/416)	
Internationa	l applic	ation No.	International filing date (day/r	month/year)	Priority date (day/month/year)	
PCT/EP98/07215 09/11/1998 07/11/1997						
International C08K5/00		t Classification (IPC) or na	L tional classification and IPC	,		
Applicant						
BOREAL	IS A/S	S et al.				
1. This ir and is	nterna transi	tional preliminary exami mitted to the applicant a	nation report has been pre according to Article 36.	pared by this In	ternational Preliminary Examining Authority	
2. This P	REPOR	RT consists of a total of	4 sheets, including this co	er sheet.		
be (s	een an ee Ru	nended and are the bas le 70.16 and Section 60	is for this report and/or she 07 of the Administrative Inst	ets containing	ion, claims and/or drawings which have rectifications made before this Authority the PCT).	
Inese	anne	xes consist of a total of	o sneets.			
3. This re	eport o	contains indications rela	ting to the following items:			
1		Basis of the report				
II.		Priority			P 1994	
III				y, inventive ste	p and industrial applicability	
V V	\boxtimes				ventive step or industrial applicability;	
VI		Certain documents cite	·			
VII		Certain defects in the in				
VIII			n the international application	on		
Date of sub	missior	n of the demand	Da	te of completion	of this report	
20/05/19	99			0 8. 62. 60		
	examir	address of the international	AL AL	thorized officer	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
9))		pean Patent Office 298 Munich	l H	ein. F	(1) (1) (1) (1) (1) (1) (1) (1) (1) (1)	
Tel. +49 89 2399 - 0 Tx: 523656 epmu d Fax: +49 89 2399 - 4465				lenhone No. +49	89 2299 2134	

INTERNATIONAL PRELIMINARY **EXAMINATION REPORT**

International application No. PCT/EP98/07215

I.	Basis	of	the	rej	port
----	-------	----	-----	-----	------

1.	This report has been drawn on the basis of (substitute sheets which have been furnished to the receiving Office in
	response to an invitation under Article 14 are referred to in this report as "originally filed" and are not annexed to
	the report since they do not contain amendments.):

		oonse to an invitation report since they d					to in this repo	rt as "originally filed	i" and are not annexed to
	Des	cription, pages:							
	1,2, 14-	4,5,7-12, 19	as ori	iginally t	filed				
	3,6,	13	as red	ceived (on		03/12/1999	with letter of	03/12/1999
	Cla	ims, No.:							
	1-1	3	as red	ceived (on		03/12/1999	with letter of	03/12/1999
2.	The	amendments have	e resul	ted in th	ie cancel	lation of:			
		the description,	pa	ges:					
		the claims,	No	s.:					
		the drawings,	she	eets:					
3.	⊠	This report has be considered to go b						nts had not been ma	ade, since they have been
		see separate she	et						
4.	Ado	litional observations	s, if ne	cessary	/ :				
V.		soned statement licability; citation						inventive step or i nent	industrial
1.	Sta	tement							
	Nov	relty (N)		Yes: No:	Claims Claims	1-13			
	Inve	entive step (IS)		Yes: No:	Claims Claims	1-13			
	Indi	ustrial applicability ((IA)	Yes:	Claims	1-13			

2. Citations and explanations

see separate sheet

VIII. Certain observations on the international application

The following observations on the clarity of the claims, description, and drawings or on the question whether the claims are fully supported by the description, are made:

see separate sheet

R Item I

Basis of the report

The applicant has not indicated the passage(s) of the application as filed on which the amendments to operative Claims 3 and 11 are based.

These amendments are considered to contravene Art. 34(2)(b) PCT.

Re Item V

Reasoned statement under Rule 66.2(a)(ii) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement

Reference is made to the following documents:

D1: EP-A-0 152 701 (cited in the application)

D2: EP-A-0 151 883 D3: GB-A-1 104 665

The claimed subject-matter differs from the teaching of D1 - D3 in that the concentration of the colour pigment is defined.

The prior art documents on file are silent on shrinkage problems associated with pigment-containing propylene polymer compositions.

Therefore, the subject-matter of Claims 1-13 is regarded to meet the requirements of Art. 33 (2)-(4) PCT.

Re Item VIII

Certain observations on the international application

Claims 3 and 11 are unclear since the conditions under which the shrinkage occurs are not defined (Art. 6 PCT).

Reference is made in this respect to the last par. at p. 13, which refers to a variation in shrinkage in both flow and cross direction of less than 5 % for white, red and blue pigments (compared to conventional, non-nucleated polymers).

•The demand with the on	d must be filed directly with the e chosen by the applicant. The f	spetent International Preliminary Examining Authorill name or two-letter code of that Authority may be in	or, if two or more Authorities are competent
TTD TO 4 4	EP		

PCT

CHAPTER II

DEMAND

under Article 31 of the Patent Cooperation Treaty:

The undersigned requests that the international application specified below be the subject of international preliminary examination according to the Patent Cooperation Treaty and hereby elects all eligible States (except where otherwise indicated).

For	r International Preliminar	y Examining Authorit	y use only
Identification of IPEA		Date of receipt of D	DEMAND
Box No. 1 IDENTIFICATION OF T	HE INTERNATIONAL	APPLICATION	Applicant's or agent's file reference BOR 10 PCT
International application No. PCT/EP98/07215	International filing date (09.11.1998 9 November	e (day/month/year) 3) 1998	(Earliest) Priority date (day/month/year) (07.11.1997) 7 November 1997
Title of invention Coloured polypropylene of	compositions		
Box No. II APPLICANT(S)			
Name and address: (Family name followed by a The address must include p	given name; for a legal entity, f postal code and name of coun	full official designation. try.)	Telephone No.:
Lyngby Hovedgade 96 DK-2800 Lyngby Denmark			Facsimile No.:
Defilial K			Teleprinter No.:
State (that is, country) of nationality: Denmark		State (that is, country Denmark	
Name and address: (Family name followed by g CROZIER, Hérve Ekliveien 37 N-3960 Stathelle Norway	çiven name; for a legal entity, f	ull official designation. The	e address must include postal code and name of country.)
State (that is, country) of nationality: Norway		State (that is, country Norway	y) of residence:
Name and address: (Family name followed by g FOLLAND, Rick Chemin des Hougardiers 3 Melin B-1370 Jodoigne Belgium		ull official designation. The	e address must include postal code and name of country.)
State (that is, country) of nationality: Belgium		State (that is, country Belgium	y) fresidence:
Further applicants are indicated on a	a continuation sheet.	<u> </u>	

Sheet	NI.	2	
SHEEL	INO.		

International application No. PCT/EP98/07215

Box No. III AGENT OR COMMON REPRESENTATIVE; OR ADDRESS FOR CORRESPONDENCE							
The following person is X agent common representative							
and X has been appointed earlier and represents the applicant(s) also for international preliminary examination.							
is hereby appointed and any earlier appointment of (an) agent(s)/common representative is hereby revoked.							
is hereby appointed, specifically for the procedure before the International Prelimi							
the agenity/common representative appointed earlier.							
Name and address: (Family name followed by given name; for a legal entity, full official designation. The address must include postal code and name of country.) Telephone No.:							
LAINE, Seppo; SUNDMAN, Christoffer; +358-9-68 59 560							
LIPSANEN, Jari; HOVI, Simo; and KNUTH-LEHTOLA, Sisko	Facsimile No.:						
of SEPPO LAINE OY	+358-9-68 59 56 10						
Itämerenkatu 3 B, FIN-00180 Helsinki, Finland	Teleprinter No.:						
·	•						
Address for correspondence: Mark this check-box where no agent or common re	Lepresentative is/has been appointed and the						
special address to which correspondence	should be sent.						
Box No. IV BASIS FOR INTERNATIONAL PRELIMINARY EXAMINATION							
Statement concerning amendments:* 1. The applicant wishes the interpotional preliminary was instituted as a second secon							
1. The applicant wishes the international preliminary examination to start on the basis of: the international application as originally filed	•						
the description as originally filed	•						
as amended under Article 34							
the claims as originally filed							
as amended under Article 19 (together with any accompanying statement) as amended under Article 34							
the drawings as originally filed							
as amended under Article 34							
2 The applicant wishes any amendment to the claims under Article 19 to be considered as reversed.							
3. The applicant wishes the start of the international preliminary examination to be postponed until the expiration of 20 m nths							
under Article 19 or a notice from the applicant that he does not wish to make such amendments (Rule 69 1(d)). (This check							
box may be marked only where the time limit under Article 19 has not yet expired.)							
as originally filed or, where a copy of amendments to the claims under Article 19 and/or amendments of the international application under Article 34 are received by the International Preliminary Examining Authority before it has begun to draw up a written pinion or the international preliminary examination report, as so amended.							
Language for the purposes of international preliminary examination: English							
x which is the language in which the international application was filed.							
which is the language of a translation furnished for the purposes of internation	nal search.						
which is the language of publication of the international application.							
which is the language of the translation (to be) furnished for the purposes of interr	national preliminary examination.						
Box N . V ELECTION OF STATES	-						
The applicant hereby elects all eligible States (that is, all States which have been designate the PCT)	ed and which are bound by Chapter II of						
excluding the following States which the applicant wishes not to elect:							

International application No. Sheet No. 3 PCT/EP98/07215 Box No. VI CHECK LIST For International Preliminary The demand is accompanied by the following elements, in the language referred to in Examining Authority use only Box No. IV, for the purposes of international preliminary examination: received not received 1. translation of international application sheets 2. amendments under Article 34 sheets 3. copy (or, where required, translation) of amendments under Article 19 sheets 4. copy (or, where required, translation) of statement under Article 19 sheets 5. letter sheets 6. other (specify) sheets The demand is also accompanied by the item(s) marked below: fee calculation sheet statement explaining lack of signature separate signed power of attorney nucleotide and or amino acid sequence listing in computer readable form copy of general power of attorney; reference number, if any: other (specify): Box No. VII SIGNATURE OF APPLICANT, AGENT OR COMMON REPRESENTATIVE Next to each signature, indicate the name of the person signing and the capacity in which the person signs (if such capacity is not obvious from reading the demand). For the Applicants Seppo Laine Oy Christoffer Sundman

For International Preliminary Examining Authority use only					
Date of actual receipt of DEMAND:					
2. Adjusted date of receipt of demand due to CORRECTIONS under Rule 60.1(b):					
The date of receipt of the demand is AFTER the expiration of 19 months from the priority date and item 4 or 5, below, does not apply.	The applicant has been informed accordingly.				
4. The date of receipt of the demand is WITHIN the period of 19 months from Rule 80.5.	om the priority date as extended by virtue of				
5. Although the date of receipt of the demand is after the expiration of 19 mont is EXCUSED pursuant t Rule 82.	ths from the priority date, the delay in arrival				
F r International Bureau use only					

Form PCT/IPEA/401 (last sheet) (July 1998; reprint January 1999)

Demand received from IPEA on:

See Notes to the demand form

PCT

REQUEST

International Application No.	
International Filing Date	
Name of receiving Office and "PCT International Application	cation"

	International Filing Date			
The undersigned requests that the present				
international application be processed	Name of receiving Office and "PCT International Application"			
according to the Patent Cooperation Treaty.				
<u> </u>	Applicant's or agent's file (if desired) (12 characters n	UND IN DOT		
Box No. I TITLE OF INVENTION				
Coloured p	colypropylene com	mpositions		
Box No. II APPLICANT				
Name and address: (Family name followed by given name: for a ladesignation. The address must include postal code and name of coulodress indicated in this Box is the applicant's State (that is, country, of residence is indicated below.)	legal entity, full official ntry. The country of the) of residence if no State	This person is also inventor.		
BOREALIS A/S		Telephone No.		
Lyngby Hovedgade 96 DK-2800 Lyngby Denmark		Facsimile No.		
		Teleprinter No.		
State (that is, country) of nationality: Denmark	State (that is, country) Denmark	of residence:		
This person is applicant all designated for the purposes of:		United States the States indicated in the Supplemental Box		
Box No. III FURTHER APPLICANT(S) AND/OR (FURTH	HER) INVENTOR(S)			
Name and address: (Family name followed by given name; for a legal entity, full official designation. The address must include postal code and name of country. The country of the address indicated in this Box is the applicant's State (that is, country) of residence if no State of residence is indicated below.) CROZIER, Hérve				
Ekliveien 37		x applicant and inventor		
N-3960 Stathelle Norway		inventor only (If this check-box		
		is marked, do not fill in below.)		
State (that is, country) of nationality:	State (that is, country) o	of residence:		
Norway This person is applicant all designated all designated	<u> </u>	e United States		
for the purposes of: States the United St		e United States indicated in the Supplemental Box		
X Further applicants and/or (further) inventors are indicated o				
Box No. IV AGENT OR COMMON REPRESENTATIVE;		ORRESPONDENCE		
The person identified below is hereby/has been appointed to act of of the applicant(s) before the competent International Authorities a	as: X a	gent common representative		
Name and address: (Family name followed by given name; for a designation. The address must include postal co		Telephone No. +358-9-68 59 560		
LAINE, Seppo; SUNDMAN, Christoffer LIPSANEN, Jari; HOVI, Simo; and	"	Facsimile No.		
KNUTH-LEHTOLA, Sisko		+358-9-68 59 56 10		
of SEPPO LAINE OY Itämerenkatu 3 B, FIN-00180 Helsir	nki,	Teleprinter No.		
Finland				
Address for correspondence: Mark this check-box where n space above is used instead to indicate a special address to w	o agent or common repres hich correspondence shou	entative is/has been appointed and the ald be sent.		

Sheet	No		2

Continuation of Box No. III FURTHER APPLICANT(S) AND/OR (FURTHER) INVENTOR(S)					
If none of the following sub-boxes is used, th	is sheet should not be inc	cluded in the request.			
Name and address: (Family name followed by given name; for a le designation. The address must include postal code and name of cour address indicated in this Box is the applicant's State (that is. country) of residence is indicated below.) FOLLAND, Rick Chemin des Hougardiers 3 Melin B-1370 Jodoigne Belgium	This person is: applicant only applicant and inventor inventor only (If this check-box is marked, do not fill in below.)				
State (that is, country) of nationality: Belgium	State (that is country) (Belgium	of residence:			
This person is applicant all designated all designated		e United States			
Name and address: (Family name followed by given name; for a le designation. The address must include postal code and name of cour address indicated in this Box is the applicant's State (that is, country) of residence is indicated below.)	egal entity, full official siry. The country of the of residence if no State	This person is: applicant only applicant and inventor inventor only (If this check-box is marked, do not fill in below.)			
State (that is, country) of nationality:	State (that is, country)	of residence:			
This person is applicant all designated for the purposes of:		United States the States indicated in the Supplemental Box			
Name and address: (Family name followed by given name; for a le designation. The address must include postal code and name of cour address indicated in this Box is the applicant's State (that is, country) of residence is indicated below.)	egal entity, full official arry. The country of the of residence if no State	This person is: applicant only applicant and inventor inventor only (If this check-box is marked, do not fill in below.)			
State (that is, country) of nationality:	State (that is, country)	of residence:			
This person is applicant all designated all designated for the purposes of:		e United States America only the States indicated in the Supplemental Box			
Name and address: (Family name followed by given name; for a l designation. The address must include postal code and name of cour address indicated in this Box is the applicant's State (that is, country, of residence is indicated below.)	ntry. The country of the	This person is: applicant only applicant and inventor inventor only (If this check-box is marked, do not fill in below.)			
State (that is, country) of nationality:	State (that is, country)	of residence:			
This person is applicant all designated for the purposes of:		the United States indicated in the Supplemental Box			
Further applicants and/or (further) inventors are indicated on another continuation sheet.					

	No.V	DESIGNATION OF STATES							
The	follow	ring designations are hereby made under Rule 4.9(a)	mark	the ap	plicable check-boxes; at least one must be marked):				
Reg	ional I	Patent			·				
N.	AP	ARIPO Patent: GH Ghana. GM Gambia, KE Kenya, LS Lesotho, MW Malawi. SD Sudan. SZ Swaziland, UG Uganda. ZW Zimbabwe, and any other State which is a Contracting State of the Harare Protocol and of the PCT							
⊠	EA	Eurasian Patent: AM Armenia. AZ Azerbaijan, BY Belarus, KG Kyrgyzstan. KZ Kazakhstan, MD Republic of Moldova. RU Russian Federation, TJ Tajikistan, TM Turkmenistan, and any other State which is a Contracting State of the Eurasian Patent Convention and of the PCT							
X	EP	European Patent: AT Austria, BE Belgium, CH and LI Switzerland and Liechtenstein, CY Cyprus, DE Germany, DK Denmark, ES Spain, FI Finland, FR France, GB United Kingdom, GR Greece, IE Ireland, IT Italy, LU Luxembourg, MC Monaco, NL Netherlands, PT Portugal, SE Sweden, and any other State which is a Contracting State of the European Patent Convention and of the PCT							
X	OA	OAPI Patent: BF Burkina Faso. BJ Benin, CF Central African Republic, CG Congo, CI Côte d'Ivoire, CM Cameroon. GA Gabon, GN Guinea, ML Mali, MR Mauritania, NE Niger, SN Senegal, TD Chad, TG Togo, and any other State which is a member State of OAPI and a Contracting State of the PCT (if other kind of protection or treatment desired, specify on dotted line)							
Natio	onal P	atent (if other kind of protection or treatment desired							
[X]		Albania	. <i>1</i> 20		Lesotho				
		Armenia	図		Lithuania				
⊠ ⊠		Austria	[3]		Luxembourg				
X		Australia	[2]		Latvia				
		Azerbaijan							
		Bosnia and Herzegovina			Republic of Moldova				
		Barbados	[X]		Madagascar				
⊠			X	IVIK	The former Yugoslav Republic of Macedonia				
ZI ZI		Bulgaria	ব্য	2421	N				
		Brazil	X		Mongolia				
X		Beiarus	X		Malawi				
<u>X</u>		Canada	Ø		Mexico				
XI XI		and LI Switzerland and Liechtenstein	Z		Norway				
		China	図		New Zealand				
Ø		Cuba	図		Poland				
図		Czech Republic	X		Portugal				
図		Germany	X		Romania				
X		Denmark	X	RU	Russian Federation				
X		Estonia	X	SD	Sudan				
·X	ES	Spain	X	SE	Sweden				
区	FI	Finland	X	SG	Singapore				
X		United Kingdom	X	SI	Slovenia				
図		Georgia	X	SK	Slovakia				
図		Ghana	X		Sierra Leone				
\square		Gambia	X	TJ	Tajikistan				
\Box		Guinea-Bissau	X	TM	Turkmenistan				
X	HR	Croatia	X	TR	Turkey				
\boxtimes	HU	Hungary	X		Trinidad and Tobago				
X	ID	Indonesia	X		Ukraine				
X	IL	Israel	\mathbf{X}	UG	Uganda				
X	IS	Iceland	\mathbf{x}		United States of America				
X	JP	Japan							
X	KE	Kenya	\mathbf{x}	UZ	Uzbekistan				
\mathbf{x}	KG	Kyrgyzstan	X		Viet Nam				
X	KP	Democratic People's Republic of Korea	\mathbf{x}		Yugoslavia				
			<u> </u>		Zimbabwe				
X	KR	Republic of Korea							
X		Kazakhstan	a na	tional	xes reserved for designating States (for the purposes of patent) which have become party to the PCT after				
X	LC	Saint Lucia Saint Lucia Saint Lucia Saint Lucia							
\mathbf{x}	LK	Sri Lanka							
X		<u> </u>							
		Liberia							

Precautionary Designation Statement: In addition to the designations made above, the applicant also makes under Rule 4.9(b) all other designations which would be permitted under the PCT except any designation(s) indicated in the Supplemental B x as being excluded from the scope of this statement. The applicant declares that those additional designations are subject to confirmation and that any designation which is not confirmed before the expiration of 15 months from the priority date is to be regarded as withdrawn by the applicant at the expiration of that time limit. (Confirmation of a designation consists of the filing of a notice specifying that designation and the payment of the designation and confirmation fees. Confirmation must reach the receiving Office within the 15-month time limit.) Sheet No.

Box No. VI PRIORITY C	LAIM	Further prior	Further priority claims are indicated in the Supplemental Box.					
Filing date	Number		Where earlier application is:					
of earlier application (day/month/year)	of earlier applicatio	national application:	regional application:* regional Office	international application: receiving Office				
item (1)(07.11.1997) 7 November 1997	974177	Finland						
item (2)								
item (3)								
The receiving Office is requested to prepare and transmit to the International Bureau a certified copy of the earlier application(s) (only if the earlier application was filed with the Office which for the purposes of the present international application is the receiving Office) identified above as item(s):								
* Where the earlier application is Convention for the Protection of li	an ARIPO application, it	t is mandatory to indicate in the S sich that earlier application was fil	upplemental Box at least (led (Rule 4.10(h)(ii)). See	one country party to the Paris Supplemental Box				
	NAL SEARCHING		, , , , , , , , , , , , , , , , , , ,					
Choice of International Searching Authority (ISA) (if two or more International Searching Authorities are competent to carry out the international search, indicate the Authority chosen; the two-letter code may be used): Request to use results of earlier search; reference to that search (if an earlier search has been carried out by or requested from the International Searching Authority): Date (day/month/year) Number Country (or regional Office)								
ISA / EP								
Box No. VIII CHECK LIST	; LANGUAGE OF I	FILING						
This international application of the following number of sheet	:s:	ational application is accompantal	nied by the item(s) mark	ed below:				
request .		rate signed power of attorneyS	(2)					
description (excluding sequence listing part)	L9 3. <u>□</u> copy	of general power of attorney;	reference number, if an	y:				
claims : 3	3 4. ☐ state:	ment explaining lack of signatu	ıre					
abstract :	L 5. ☐ prior	rity document(s) identified in B	sox No. VI as item(s):					
drawings : -		slation of international applicati						
sequence listing part of description	- - '	ate indications concerning deposited microorganism or other biological material						
Total number of sheets:	8. ☐ nucle 27 9. ☐ other	eotide and/or amino acid seque r <i>(specify)</i> :	nce listing in computer	readable form				
Figure of the drawings which should accompany the abstract		Language of filing of the international application:	English					
Box No. IX SIGNATURE	OF APPLICANT OR	RAGENT						
Next to each signature, indicate the n	ame of the person signing a	nd the capacity in which the person si	igns (if such capacity is not o	bvious from reading the request).				
For the Appli	cants	Sep	po Laine Oy	·				
Christoffer Sundman								
		For receiving Office use only						
1. Date of actual receipt of the purported international application: 2. Drawings:								
3. Corrected date of actual receipt due to later but timely received papers or drawings completing the purported international application:								
4. Date of timely receipt of the required corrections under PCT Article 11(2):								
5. International Searching Authority (if two or more are competent): ISA / 6. Transmittal of search copy delayed until search fee is paid.								
Date of receipt of the record copy by the International Bureau:								

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6: C08K 5/00, C08L 23/10

(11) International Publication Number:

WO 99/24503

(43) International Publication Date:

20 May 1999 (20.05.99)

(21) International Application Number:

PCT/EP98/07215

A1

(22) International Filing Date:

9 November 1998 (09.11.98)

(30) Priority Data:

974177

7 November 1997 (07.11.97)

FI

(71) Applicant (for all designated States except US): BOREALIS A/S [DK/DK]; Lyngby Hovedgade 96, DK-2800 Lyngby (DK).

(72) Inventors; and

(75) Inventors/Applicants (for US only): CROZIER, Hérve [NO/NO]; Ekliveien 37, N-3960 Stathelle (NO). FOL-LAND, Rick [BE/BE]; Chemins des Hougardiers 3, Melin, B-1370 Jodoigne (BE).

(74) Agents: LAINE, Seppo et al.; Seppo Laine Oy, Itämerenkatu 3 B, FIN-00180 Helsinki (FI).

(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR. BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published

With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: COLOURED POLYPROPYLENE COMPOSITIONS

(57) Abstract

The present invention concerns coloured polymer compositions and a process for the preparation thereof. The present composition comprises a propylene polymer nucleated with a polymeric nucleating agent containing vinyl compound units and having an at least 7 °C higher crystallization temperature than that of the corresponding non-nucleated polymer, and a colour pigment having a nucleating effect on the propylene polymer. The shrinkage of the composition varies less than 5 % for different colour pigments.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Słovakia
AТ	Austria	FR	France	LU	Luxembourg	SN	Senegal
ΑŪ	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
ΑZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	zw	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

1

PCT/EP98/07215

COLOURED POLYPROPYLENE COMPOSITIONS

Background of the Invention

5 Field of the Invention

The present invention relates to coloured polymer compositions. In particular, the present invention concerns compositions of propylene homo- and copolymers suitable for caps and closures and similar polymer articles. The invention also concerns a process for preparing such compositions. Finally, the present invention relates to the use of the new propylene polymers or copolymers for the manufacture of products by melt stage processing, e.g., by blow moulding, thermoforming, injection moulding and sheet or film extrusion.

Description of Related Art

15

20

10

To an increasing extent, caps and closures of various design for drinks, food, household, hygiene, health-care, oils and chemicals and other applications are nowadays manufactured from polymeric materials. This is partly due to the requirement for high productivity, i.e. short processing cycle, which becomes crucial for the mass production of carbonated soft drinks caps that are usually obtained by either injection moulding or compression moulding techniques.

Propylene homo- and copolymers having excellent resistance to heat and chemicals as well as attractive mechanical properties, such as stiffness and impact resistance, are becoming a particularly interesting materials for these applications.

25

30

There are, however, some problems related to the prior art. Thus, nearly all caps and closures manufactured from polymeric materials are coloured. It has been experienced that pigments may have a nucleating effect on polypropylene and variation in intensity of this effect from one colour to another will result in dimensional variations because of differences in the shrinkage associated with the nucleation.

WO 99/24503

2

PCT/EP98/07215

Summary of the Invention

It is an object of the present invention to eliminate the problems related to the prior art and to provide novel coloured polypropylene compositions having consistent shrinkage and improved mechanical properties highly suited to the manufacture of injection moulded or compression moulded products which can be used as caps and closures.

A second object of the invention is to provide a process for preparing novel polypropylene compositions of the above kind.

10

15

20

25

30

5

It is still a further object of the present invention to provide products of polypropylene compositions by injection moulding or compression moulding techniques.

These and other objects, together with the advantages thereof over known processes and products, which shall become apparent from the specification which follows, are accomplished by the invention as hereinafter described and claimed.

The invention is based on blending colouring pigments with propylene homo- or copolymers nucleated for high crystallinity. In connection with the present invention it has been found that nucleating the PP resin may reduce the differences between the various degrees of shrinkage of polymer compositions coloured with different pigments. However, conventional inorganic or organic nucleating agents, e.g. talc, are either too weak to have a dominating effect or they can give rise to undesired reactions with the pigments. The conventional agents can also be difficult to disperse and there can be restrictions on food contact approvals (e.g. NaBz). Some are non-economical (e.g. sorbitol derivatives) for use for PP for caps and closures.

According to the present invention, the pigments are therefore blended with propylene polymers or copolymers nucleated with polymeric vinyl compounds to provide coloured polypropylene compositions having a consistent shrinkage during melt processing irrespective of the colouring pigment used.

5

10

15

25

30

3

The use of vinyl compounds, such as polymers of vinyl cycloalkanes and 3-methyl-1-butene, as nucleating agents in the form of reactor made blends of polypropylene and polymerised vinyl compounds or polypropylene compounds, is suggested in the prior art. cf. EP Patent Specifications Nos. 0 152 701, 0 151 883, 0 368 577 and 0 417 319.

However, none of the prior art publications makes any reference to the use of these highly unucleated materials for the production of coloured caps and closures.

According to the present invention it has now surprisingly been found that propylene homo- or copolymers nucleated with a component containing polymerized vinyl compound units will give excellent dimensional consistency by dominating the pigments' nucleating effect with its strong nucleation. The strongly nucleating effect of the polymeric nucleating agent is apparent from the high crystallisation temperature of the polymer. Thus, the crystallisation temperature of the material is at least 7 °C, preferably 10 °C and in particular over 13 °C higher than the crystallisation temperature of the corresponding non-nucleated polymer and the material exhibits a fast crystallisation rate. Caps of various colours moulded with a polypropylene nucleated with a polymerised vinyl compound grade to provide a composition according to the present invention will therefore have practically the same dimensions.

More specifically, the polymer composition according to the present invention is characterized by what is stated in the characterizing part of claim 1.

The process according to the present invention for preparing coloured polypropylene compositions is characterized by what is stated in the characterizing part of claim 9.

The present compositions can be used in any kind of polymer articles. Particular advantages are obtained by applying the compositions to the manufacture of injection moulded and/or compression moulded products as well as articles produced by thermoforming, blow moulding and film and sheet extrusion.

The invention achieves a number of considerable advantages. In particular it should be pointed out that the strong nucleating effect of a polymeric nucleating agent containing

polymerized vinyl compound units will give potential for cycle time reduction because solidification in the mould will happen earlier and faster compared to any other PP grade nucleated with conventional nucleating agents. There are also other benefits of the present invention compared to the use of additive nucleating agents that are of particular interest for the manufacture of caps and closures: the invention will provide for a reduction of the number and amount of additives. The polymeric nucleating agents are inert towards other additives/pigments, they give no taste and odour, no migration / plate out, excellent dispersion of the nucleating effect and more consistent nucleation. These positive effects are accompanied with clearly smaller amounts of the polymeric nucleating agents compared to additive nucleation.

The characteristics of the polymer compositions can easily be tailored in respect to MFR, type of polymer (homopolymer, copolymer, impact modified ...) as well as in respect to physical properties.

15

10

5

Next, the invention will be more closely examined with the aid of the following detailed description.

Detailed Description of the Invention

20

The compositions of the present invention include a polymeric component comprising a propylene polymer nucleated with polymerized vinyl compounds together with at least one colouring agent. The compositions can contain other components known in the art, such as adjuvents, additives and fillers.

25

30

The colouring agent used in the present invention can be any colouring pigment, organic or inorganic, having a nucleating effect of various strength on propylene homo- or copolymers. By dominating the nucleating effect, if any, of the pigment, the nucleated propylene homo- or copolymer will provide a controlled and predictable shrinkage irrespective of the pigment.

Examples of colouring pigments are white pigments, such as titanium dioxide,

yellow/orange pigments such as isoindolinone or azocondensation, red/violet such as quinacridone or diketo pyrrolo pyrol, blue/green pigments such as ultramarine blue or Cu Phtalocyanine blue, and black pigments such as carbon black. The amount of pigments is usually 0.01 to 5 % by weight of the polypropylene component.

5

For the purpose of the present invention, the terms "colouring agent" and "colouring pigment" are interchangeably used for designating any material used to give the final product a desired colour which is different from the one it would have without the use of that specific material.

10

15

The main component of the present compositions is the nucleated propylene polymer which contains a polymerized vinyl compound in an amount of 0.0001 to 1 %, in particular about 5 to 1000 ppm, by weight of the composition. By this nucleation it is possible to attain a polypropylene having a high degree of crystallinity, a high crystallization temperature, small crystal size and a great crystallization rate. These kinds of compositions can be used for the preparation of moulded products. They exhibit improved optical and physical properties.

20

The nucleation of the propylene polymers can be carried out by modifying the polymerization catalyst with vinyl compounds and using the modified catalyst for polymerization of propylene optionally in the presence of comonomers to provide a propylene homopolymer or copolymer containing about 0.0001 to 1 % (calculated from the weight of the composition) polymerized vinyl compounds. Another approach for nucleating propylene polymers comprises blending polypropylene with polymers containing vinyl compound units.

25

30

For the purpose of the present invention "vinyl compounds" are compounds having the formula I

6

wherein R₁ and R₂ together form a 5 or 6 membered saturated or unsaturated or aromatic ring or they stand independently for a lower alkyl comprising 1 to 4 carbon atoms.

The following specific examples of vinyl compounds can be mentioned: vinyl cycloalkanes, in particular vinyl cyclohexane, vinyl cyclopentane, vinyl-2-methyl cyclohexane and vinyl norbornane. 3-methyl-1-butene, styrene, p-methyl-styrene, 3-ethyl-1-hexene or mixtures thereof. Vinyl cyclohexane (VCH) is a particularly preferred monomer but, for example, 3-methyl-1-butene can be used as a monomer or comonomer to adjust the crystallisation temperature.

10

15

20

25

30

5

For the purpose of the present invention "nucleated propylene polymer" stands for a polymer having an increased and controlled degree of crystallinity preferably amounting to over 50 % and preferably having a crystallization temperature of more than 7 °C, preferably over 10 °C and in particular over 13 °C of the T_{cr} of the corresponding non-nucleated polymer. Using MgCl₂-supported high-yield Ziegler-Natta catalysts crystallization temperatures of more than 120 °C, preferably over 124 °C and in particular over 126 °C can be obtained. In compositions containing colouring pigments having a nucleating effect, particularly advantageous results are obtained by using polymers having a crystallization temperature over 15 °C higher than that of the corresponding non-nucleated polymer (for a polymer produced with the above-mentioned ZN-catalyst, 128 °C).

According to a preferred embodiment of the present invention, modification of the catalyst by polymerizing a vinyl compound, such as VCH, in the presence thereof is performed in an inert fluid which does not dissolve the polymer formed (e.g. polyVCH). One particularly preferred polymerization medium comprises a viscous substance, in the following a "wax", such as an oil or a mixture of an oil with a solid or semi-solid polymer (oil-grease). The viscosity of such a viscous substance is usually 1,000 to 15,000 cP at room temperature. The advantage of wax prepolymerization is that the catalyst can be prepolymerized, stored and fed into the process in the same media and catalyst wax preparation and prepolymerization is performed in the same process device. Due to the fact that no washing, drying, sieving and transferring thus are needed, the catalyst activity

is maintained (cf. Finnish Patent No. 95387). The present process is inexpensive because high catalyst concentrations and high PP production capacities can be used. Also the amount of waste is diminished because the medium used during polymerization of the vinyl compound does not have to be removed.

5

10

According to another preferred embodiment, the method for improving the crystallinity and transparency of polypropylene by blending a crystalline polypropylene with a vinyl cycloalkane polymer is carried out by melt-kneading the crystalline polypropylene with the crystal nucleating agent, compounding the crystal nucleating agent or reactor made blend of the crystal nucleating agent and PP with the crystalline polypropylene and melt kneading the mixture during film formation, and compounding the master batch of the crystal nucleating agent with the crystalline polypropylene.

The vinyl compound units of the blending and compounding process can be derived from any of the units identified in the above formula I in connection with the first embodiment of the invention.

20

15

As catalyst any stereospecific catalyst for propylene polymerization can be used, which is capable of catalyzing polymerization and copolymerization of propylene and comonomers at a pressure of 10 to 100 bar, in particular 25 to 80 bar, and at a temperature of 40 to 110 °C, in particular 60 to 110 °C. Ziegler-Natta as well as metallocene catalysts can be used.

25

Generally, the Ziegler-Natta catalyst used in the present invention comprises a catalyst component, a cocatalyst component, an external donor, the catalyst component of the catalyst system primarily containing magnesium, titanium, halogen and an internal donor.

Examples of suitable catalyst systems are described in, for example, Finnish Patents Nos. 86866, 96615 and 88047 and 88048.

30

One particularly preferable catalyst, which can be used in the present invention, is disclosed in FI Patent No. 88047. Another preferred catalyst is disclosed in Finnish Patent Application No. 963707.

8

A catalyst system useful in the present process can be prepared by reacting a magnesium halide compound with titanium tetrachloride and an internal donor. The magnesium halide compound is, for example, selected from the group of magnesium chloride, a complex of magnesium chloride with a lower alkanol and other derivatives of magnesium chloride. MgCl₂ can be used as such or it can be combined with silica, e.g. by absorbing the silica with a solution or slurry containing MgCl₂. The lower alkanol used can be preferably methanol or ethanol, particularly ethanol.

5

10

15

20

25

30

The titanium compound used in the preparation of the procatalyst is preferably an organic or inorganic titanium compound, having an oxidation state of titanium of 3 or 4. Also other transition metal compounds, such as vanadium, zirconium, chromium, molybdenum and tungsten compounds can be mixed with the titanium compound. The titanium compound usually is halide or oxyhalide, an organic metal halide, or a purely metal organic compound, in which only organic ligands have been attached to the transition metal. Particularly preferable are the titanium halides, especially TiCl₄. Preferably the titanation is carried out in two or three steps.

The Ziegler-Natta catalyst used can also be an heterogeneous unsupported TiCl₃ based catalyst. This kind of catalysts are typically solid TiCl₃ in a delta crystalline form which are activated with aluminium-chloride-alkyls, such as diethylaluminiumchloride. The solid TiCl₃ catalyst are typically prepared by reduction of TiCl₄ with aluminium-alkyls and/or aluminium-chloride-alkyls, possibly combined with heat treatment to maximise the desired delta crystalline form of TiCl₃. The performance, especially stereospecificity, of these catalyst can be improved by using Lewis-bases (electron donors), such as esters, ethers or amines.

The activity and stereospecificity of these heterogeneous unsupported TiCl₃ based catalysts are typically so low that propylene polymers or copolymers prepared require purification from catalyst residues and removal of some atactic non-crystalline polymer.

The alkoxy group of the phthalic acid ester used comprises at least five carbon atoms, preferably at least 8 carbon atoms. Thus, as the ester can be used for example propylhexyl

9

phthalate, dioctyl phthalate, dinonyl phthalate, diisodecyl phthalate, di-undecyl phthalate, ditridecyl phthalate or ditetradecyl phthalate.

The partial or complete transesterification of the phthalatic acid ester can be carried out e.g. by selecting a phthalic acid ester - a lower alcohol pair, which spontaneously or with the aid of a catalyst, which does not damage the procatalyst composition, transesterifies the catalyst at an elevated temperatures. It is preferable to carry out the transesterification at a temperature, which lies in the range of 110 to 150 °C, preferably 120 to 140 °C.

The catalyst prepared by the method above is used together with an organometallic cocatalyst and with an external donor. Generally, the external donor has the formula IV

$$R_nR'_mSi(R"O)_{4-n-m}$$

15 wherein

25

5

R and R' can be the same or different and they stand for a linear, branched or cyclic

aliphatic, or aromatic group;

R" is methyl or ethyl;

n is an integer 0 to 3:

20 m is an integer 0 to 3; and

n+m is 1 to 3.

The aliphatic groups in the meanings of R and R' can be saturated or unsaturated. Linear C_1 to C_{12} hydrocarbons include methyl, ethyl, propyl, butyl, octyl and decanyl. As examples of suitable saturated branched $C_{1.8}$ alkyl groups, the following can be mentioned: isopropyl, isobutyl, isopentyl, tert-butyl, tert-amyl and neopentyl. Cyclic aliphatic groups containing 4 to 8 carbon atoms comprise, e.g., cyclopentyl, cyclohexyl, methyl cyclopentyl and cycloheptyl.

A group of interesting donors is formed by strongly co-ordinating donors which form relatively strong complexes with catalyst surface, mainly with MgCl₂ surface in the presence of aluminium alkyl and TiCl₄. The donor components are characterised by a

WO 99/24503

10

PCT/EP98/07215

strong complexation affinity towards catalyst surface and a sterically large and protective hydrocarbon (R'). Such external donors can be selected from the group consisting of dicyclopentyl dimethoxysilane, diisopropyl dimethoxysilane, di-isobutyl dimethoxysilane, and di-t-butyl dimethoxysilane.

5

10

15

20

An organoaluminum compound is used as a cocatalyst. The organoaluminium compound is preferably selected from the group consisting of trialkylaluminium, dialkyl aluminium chloride and alkyl aluminium sesquichloride.

The metallocene catalyst comprises a metallocene/activator reaction product impregnated in a porous support at maximum internal pore volume. The catalyst complex comprises a ligand which is typically bridged, and a transition metal of group IVA...VIA, typically a metal halide, and aluminium alkyl. The ligands can belong to group of heterocyclic substituted or unsubstituted compouns. e.g. indocenes, naftenes, or any other bulky compound which can control the stereoselectivity of the catalyst especially when ligands are bridged together with silane or other chemical bond. The activator is selected from a group in which are derivates of water and aluminium alkyls e.g. trimethyl aluminium, triethyl aluminium. and tri t-butyl aluminium. or another compound capable of activating the complex. The metallocene/activator reaction product, a solvent capable of dissolving it, and a porous support are brought into mutual contact, the solvent is removed and the porous support is impregnated with the metallocene/activator reaction product, the maximum amount of which corresponds to the pore volume support, cf. International PCT Application No. PCT/FI94/00499.

One typical structure of metallocene compound is bridged bis(2-R-4-R'-indenyl) M Cl₂, wherein both R and R' are aliphatic, cycloaliphatic or aromatic hydrocarbons having 1 to 18 C atoms, R' is typically phenyl or naphthyl, and R is typically methyl or ethyl. M is a transition metal, typically titanium, zirconium or hafnium, R and R' may contain heteroatoms, such as silicon, nitrogen, phosphorous or germanium. The bridge between the indenyls is made from 1 to 3 atoms, such as carbon, silicon, nitrogen, phosphorous or germanium. A typical bridge is dimethylsilyl or ethyl. An example of such a metallocene compound is dimethylsilyl-bis(2-methyl-4-phenyl-indenyl)zirconium dichloride.

11

Following the modification of the catalyst with the vinyl compound of the first preferred embodiment of the invention, the catalyst is optionally prepolymerized with propylene and/or another 1-olefin to provide a prepolymerized catalyst composition which is used for polymerization of propylene optionally together with comonomers.

5

The propylene homo- or copolymer can have a unimodal or bimodal molar mass distribution. Thus, the equipment of the polymerization process can comprise any polymerization reactors of conventional design for producing propylene homo- or copolymers. For the purpose of the present invention, "slurry reactor" designates any reactor, such as a continuous or simple batch stirred tank reactor or loop reactor, operating in bulk or slurry and in which the polymer forms in particulate form. "Bulk" means a polymerization in reaction medium that comprises at least 60 wt-% monomer. According to a preferred embodiment the slurry reactor comprises a bulk loop reactor. By "gas phase reactor" is meant any mechanically mixed or fluid bed reactor. Preferably the gas phase reactor comprises a mechanically agitated fluid bed reactor with gas velocities of at least 0.2 m/sec.

15

10

Thus, the polymerization reactor system can comprise one or more conventional stirred-tank slurry reactors, as described in WO 94/26794, or one or more gas phase reactors. Preferably the reactors used are selected from the group of loop and gas phase reactors and, in particular, the process employs at least one loop reactor and at least one gas phase reactor. This alternative is particularly suitable for producing bimodal poly-propylene. By carrying out the polymerization in the different polymerization reactors in the presence of different amounts of hydrogen, the MWD (molecular mass distribution) of the product can be broadened and its mechanical properties improved. It is also possible to use several reactors of each type, e.g. one loop reactor and two or three gas phase reactors or two loop reactors and one gas phase reactor, in series.

25

30

20

In every polymerization step it is possible to use also comonomers selected from the group of ethylene, propylene, butene, pentene, hexene and alike as well as their mixtures.

In addition to the actual polymerization reactors used for producing the propylene homo-

or copolymer, the polymerization reaction system can also include a number of additional reactors, such as pre- and/or postreactors. The prereactors include any reactor for prepolymerizing the catalyst with propylene and/or other 1-olefins. The postreactors include reactors used for modifying and improving the properties of the polymer product. All reactors of the reactor system are preferably arranged in series.

5

10

15

20

25

30

The gas phase reactor can be an ordinary fluidized bed reactor, although other types of gas phase reactors can be used. In a fluidized bed reactor, the bed consists of the formed and growing polymer particles as well as still active catalyst come along with the polymer fraction. The bed is kept in a fluidized state by introducing gaseous components, for instance monomer on such flowing rate which will make the particles act as a fluid. The fluidizing gas can contain also inert carrier gases, like nitrogen and also hydrogen as a modifier. The fluidized gas phase reactor can be equipped with a mechanical mixer.

The gas phase reactor used can be operated in the temperature range of 50 to 115 °C, preferably between 60 and 110 °C and the reaction pressure between 5 and 50 bar and the partial pressure of monomer between 2 and 45 bar.

The pressure of the effluent, i.e. the polymerization product including the gaseous reaction medium, can be released after the gas phase reactor in order optionally to separate part of the gaseous and possible volatile components of the product, e.g. in a flash tank. The overhead stream or part of it is recirculated to the reactor.

The propylene homo- or copolymer produced preferably has a MWD of 2 - 10 and a MFR $_2$ in the range of 0.01 - 1500 g/10 min., in particular 0.05 - 500 g/10 min. MFR $_2$ values disclosed herein are measured according to ISO 1133. 230 °C, using 2.16 kg load.

In the second embodiment of the invention, wherein a uni- or bimodal propylene homo- or copolymer is blended and compounded with a polymer comprising vinyl compound units, the blending is carried out as known in the art using said nucleating polymeric agent.

By means of both embodiments, a propylene homopolymer or copolymer is produced with

13

high-yield Ziegler-Natta catalysts, having high stiffness, an increased overall degree of crystallization and a crystallization temperature of the propylene homopolymer fraction of more than 120 °C, preferably over 124 °C and in particular over 126 °C. The degree of crystallization for a propylene homopolymer is generally over 48 %, and often over 50 %.

5

The amount of the nucleating polymeric agent is, in case of propylene polymers or copolymers, about 0.0001 to 1 wt-%, and in case of polypropylene blends about 0.0001 to 0.5 wt-%.

10

This nucleated polypropylene (100 parts by weight) is blended with 0.01 to 5 parts by weight of the coloured pigment of choise. The particle size of the pigment is usually 0.01 to 1000 micrometre and more often 0.1 to 10 micrometre.

15

The colouring agent is usually in the form of a masterbatch comprising also a polymer carrier. The blending with the polypropylene is directly done at the conversion machine (e.g. extruder, injection moulding machine...) by dosing the pigment with a gravimetric side feeder. When the colouring agent is liquid it is dosed with a liquid pump.

20

The present polymers and copolymers of propylene can be blended and optionally compounded with additives and adjuvants conventionally used in the art. Thus, suitable additives include antistatic agents, flame retardants, light and heat stabilizers, reinforcement agents, pigments and carbon black. Fillers such as mica, CaCO₃, talc and wollastonite can also be used. Further, the polymers and copolymers can be blended with non-nucleated propylene and/or with other polymers, in particular other polyolefins, such as LD-, LLD-. MD- and HD-polyethylenes and polybutylene.

25

30

Compositions according to the invention containing pigments will exhibit very small variation in shrinkage irrespective of the colouring agent used. As the results indicated below in Example 1 show, the variation in shrinkage in both flow and cross direction is less than 5 % for white, red and blue pigments compared to conventional, non-nucleated polymers having a variation of shrinkage in the range of 10 to 20 %. The fact that the pigments' nucleating effect is clearly dominated by the nucleated polypropylene with its

14

strong nucleation is apparent from the results showing that the shrinkage is practically constant irrespective of whether or not the compositions contain any colouring pigment at all. This feature is rather surprising in particular when comparing the shrinkage of the present compositions to conventional talc-nucleated homopolymer compositions which have the same variation as non-nucleated polymer compositions (or even greater) in transversal direction to the flow.

The homopolymer or copolymer composition thus obtained can be used for the manufacture of moulded articles. in particular articles processed by blow moulding, injection moulding, compression moulding, thermoforming and sheet or film extrusion, pipe and cable extrusion.

Particularly useful products include caps and closures for various food, in particular carbonated soft drinks, household, hygiene, health-care and other applications. Further interesting products and articles include bottles, containers and pails.

Examples

5

10

15

25

30

The following non-limiting examples illustrate the invention.

Example 1

Catalyst modification with polymerisation of vinyl cycloalkane:

A high yield MgCl₂ supported TiCl₄ Ziegler-Natta catalyst prepared according to Finnish patent FI 88047 was dispersed into a mixture of oil and crease (Shell Ondina Oil N 68 and Fuchs Vaseline Grease SW in 3.2:1 Oil/grease volume ratio). The titanium content of the catalyst was 2.5 wt-%. and the concentration of the catalyst in oil-grease mixture was 176 g cat/dm³. Triethylaluminium (TEAL) was added to the catalyst dispersion in a TEAL to titanium mole ratio of 1.5. After that vinylcyclohexane (VCH) was added to the reaction mixture, and the VCH to catalyst weight ratio was 1:1. The reaction mixture was mixed in a temperature of 55 °C until the concentration of unreacted VCH in the reaction mixture

15

was 350 ppm by weight.

Example 2

Polymerisation of propylene

5

The modified catalyst in the oil grease mixture (catalyst mud) obtained from example 1, TEAL, dicyclopentyldimethoxysilane and propylene were continuously fed to a process consisting of a prepolymerisation reactor and a loop rector.

Before mixing, the TEAL and dicyclopentyldimethoxysilane in a 10.7 w/w ratio was contacted with the catalyst mud. After that the mixture was transferred with propylene, containing the desired amount of hydrogen as molecular weight regulating agent, to a continuous, stirred prepolymerisation reactor. After the prepolymerisation, the reaction mixture together with additional propylene and hydrogen was fed to a continuous loop reactor operating at 68 °C. The obtained PP homo-polymer-propylene slurry containing the catalyst was continuously recovered from the loop reactor to a flashing unit where the liquid propylene was vaporised and the remaining solid polymer particles were continuously recovered from the flashing unit. After purging the unreacted monomers, the required stabilisers and other additives were added and the polymer powder was pelletised with an extruder.

The final polymer had an MFR₂ of 25 g/10 min, and insolubles in boiling n-heptane 96.0 wt-%.

25 Example 3

30

Dimensional consistency

The PP homopolymer described in previous examples and a commercial non nucleated PP homopolymer (MFR 12) and a commercial talc-nucleated PP homopolymer (MFR35) were moulded by injection moulding (machine: Netstal 300 tons, N1570/300MPS) in the form of a box bac characterised by:

• thickness: 1.8 mm

16

length: 370 mmwidth: 185 mm

• height: 95 mm

• injection: cold runner

• max flow length: 300 mm

4 preparations for each of the 3 polypropylenes were moulded:

1. natural

10

- 2. 100 parts by weight + 2 parts by weight of white masterbatch (titanium dioxide based white pigment)
- 3. 100 parts by weight + 2 parts by weight of red masterbatch (quinacridone based red pigment)
- 4. 100 parts by weight + 2 parts by weight of dark blue masterbatch (Cu Phtalocyanine blue based blue pigment)
- 15 The preparations were blended batch-wise in a bag to prepare roughly 5 kg for each.

Typical moulding conditions were:

• Injection speed: 100 mm/sec

• Holding pressure: 300 bar

• holding pressure time: 12 sec

• cooling time: 15 sec

• cycle time: 35 sec

Dimension of the boxes were measured with an optical device between lines of grid both in flow and in transverse direction.

Shrinkage, reported in Table 1, is calculated by comparing the dimension measured to the nominal mould dimension. The cross direction has proved to be determinant in characterising the shrinkage behaviour of a PP material.

Table 1. Shrinkage (%) measured on injection moulded boxes of constant weight

		Shrinkage (%)		
Grade	Colour	Flow direction	Cross direction	
Homopolymer of	Natural	1.68	1.90	
Example 2	White	Flow direction Cross of 1.68 1 1.68 1 1.70 1 1.70 1 1.70 1 Max 0.02 0 1.71 1 1.63 1 1.79 1 Max 0.16 0 1.59 1 1.62 1 1.63 1 1.63 1	1.95	
	Colour Flow direction Natural 1.68 White 1.68 Red 1.70 Blue 1.70 Delta Max 0.02 Natural 1.71 White 1.63 Red 1.71 Blue 1.79 Delta Max 0.16 Natural 1.59 White 1.62 Red 1.63 Blue 1.63	1.93		
	Blue	1.70	1.90	
	Delta Max	0.02	0.05	
Non-nucleated PP	Natural	1.71	1.58	
homopolymer	White	1.63	1.64	
	Red	1.71	1.74	
	Blue	1.79	1.96	
	Delta Max	-0.16	0.38	
Talc-nucleated PP	Natural	1.59	1.54	
homopolymer	White	1.62	1.55	
	Red	1.63	1.71	
	Blue	1.63	1.96	
	Delta Max	0.04	0.41	

20

25

5

10

15

The non-nucleated PP homopolymer shrank to different extent with different colours. That also attested the different nucleating effect of the different pigments which were also confirmed by measuring crystallisation temperatures of the coloured boxes which were 115.8 °C, 115.7 °C, 119.5 °C and 129.3 °C for the natural, white, red, and blue respectively. Crystallisation temperature was measured by differential scanning calorimetry by weighting 3 mg sample placed in a furnace heated at 10 °C/min from room temperature to 220 °C and then cooled at 10 °C/min to room temperature to get the crystallisation exothermic peak from which the maximum gives the crystallisation temperature.

30

The talc-nucleated PP homopolymer behaved similarly to the non-nucleated PP homopolymer in the ESNs that shrinkage also varied a lot depending on the colour.

The PP homopolymer (related to the present invention) exhibited practically the same shrinkage, hence the same box dimension. for all the preparations.

Example 4

5 Cycle time

The three PP homopolymer samples mentioned in Example 3 were injection moulded in the form of caps on a Netstal 120 tons, HP 1200/445. The mould was a 3 plate mould with 4 cavities, and unscrewing of the cap's threads. The caps were oval, with inner threads, with a hinged flip top. Dimension were: length 50 mm, height 30 mm, width 38 mm, wall thickness 1.2 mm.

Table 2 indicates the moulding parameters.

Table 2. Moulding parameters

		PP homopolymer of Example 2	non-nucleated PP homopolymer	talc-nucleated PP homopolymer
MFR	g/10 min	25	12	35
injection speed	mm/ min	50	50	50
holding pressure	bar	300	500	300
holding pressure time	sec	3	3	3
cooling time	sec	9	11.5	10.5
CYCLE TIME	SEC	18.5	21	20

25

30

20

10

15

The polypropylene nucleated with a polymerised vinyl compound could be moulded with faster cycle because it started to freeze (crystallise) in the mould earlier and faster that the non-nucleated and talc-nucleated PP homopolymers. Shortest cycle time was determined by decreasing cooling time until the caps deformed at ejection because they were not solidified enough.

Example 5

Dimensional consistency

The three PP homopolymer samples of Example 3 were also injection moulded according to Example 4. The conditions were identical except for the cooling time which was 11.5 seconds for all them, for the natural but also with red and blue coloured specimens prepared as described in Example 3.

Shrinkage was measured with the height of the caps, compared to the nominal dimension.

Table 3. Shrinkage in %

Natural Red Blue PP homopolymer 1.80 1.80 1.80 of Example 2 1.71 non-nucleated PP 1.25 1.41 homopolymer 1.35 1.41 1.71 talc-nucleated PP homopolymer

20

25

15

5

10

As observed in Example 3, the polypropylene nucleated with a polymerised vinyl compound is superior to the non-nucleated and the talc-nucleated PP homopolymers in the sense that shrinkage, hence dimension, was equal for natural, red and blue caps. On the other hand, variation was observed in dimension for the non-nucleated and talc-nucleated natural, red, and blue caps.

IN THE CLAIMS:

- 1. Coloured polymer composition comprising
 - a propylene polymer nucleated with a polymeric nucleating agent containing vinyl compound units and having an at least 7 °C higher crystallization temperature than that of the corresponding non-nucleated polymer, and
 - a colour pigment.
- 2. The composition according to claim 1, wherein the colour pigment has a nucleating effect on the propylene polymer.
 - 3. The composition of claim 1 or 2, wherein the shrinkage of the composition varies less than 5 % for different colour pigments.
- 4. The polymer composition according to claim 1, wherein the propylene polymer contains about 0.0001 to 1 % by weight of units derived from a vinyl compound of the formula

$$R_2$$

20

5

10

wherein R_1 and R_2 together form a 5 or 6 membered saturated or unsaturated or aromatic ring or they stand independently for a lower alkyl comprising 1 to 4 carbon atoms.

- 5. The polymer composition according to claim 4, wherein the propylene polymer contains cycloalkane units, in particular vinyl cyclohexane, vinyl cyclopentane, vinyl-2-methyl cyclohexane and vinyl norbornane. 3-methyl-1-butene, styrene, p-methyl-styrene or 3-ethyl-hexene units or mixtures thereof.
- 6. The polymer composition according to any of claims 1 to 5, wherein the nucleated propylene polymer comprises a propylene polymer copolymer polymerized in the presence of a catalyst modified with a polymer containing vinyl compound units.

PCT/EP98/07215

- 7. The polymer composition according to any of claims 1 to 5, wherein the nucleated propylene polymer comprises a propylene homo- or copolymer blended with a polymer containing polymerised vinyl compound units.
- 8. The polymer composition according to any of the preceding claims, wherein the pigment is selected from the group of white pigments, yellow/orange pigments, red/violet pigments, blue/green pigments and carbon black.
 - 9. The polymer composition according to claim 8, wherein the pigment is selected from the group of titanium dioxide, isoindolinone, azocondensation, quinacridone, diketo pyrrolo pyrol, ultramarine blue, Cu Phtalocyanine blue and carbon black.
 - 10. The polymer composition according to any of the preceding claims, wherein the concentration of the colouring pigment is 0.01 to 5 wt-% calculated from the weight of the polypropylene component.
 - 11. A process for preparing a coloured polymer composition comprising a propylene polymer and a colour pigment, characterized by using a propylene polymer nucleated with a polymeric nucleating agent containing vinyl compound units and having an at least 7 °C higher crystallization temperature than the corresponding non-nucleated polymer.
 - 12. The process according to claim 11 wherein 100 parts by weight of a nucleated polypropylene composition containing about 0.0001 to 1 % by weight of units derived from a vinyl compound of the formula

25

10

15

20

30

$$R_2$$

wherein R₁ and R₂ together form a 5 or 6 membered saturated or unsaturated or aromatic ring or they stand independently for a lower alkyl comprising 1 to 4 carbon atoms is blended with 0.01 to 5 parts by weight of a colouring pigment selected from the group of white pigments, green pigments, red pigments, blue pigments and carbon black, to provide

22

a coloured polypropylene composition, the shrinkage of which varies less than 5 % for different colour pigments.

13. Use of a polymer composition according to any of claims 1 to 10 for the manufacture of polymer articles by injection moulding or compression moulding, thermoforming, blow moulding, film or sheet extrusion, pipe or cable extrusion.

5

14. The use of claim 13, wherein caps and closures for food, household, hygiene and health-care applications are manufactured.

a. classification of subject matter IPC 6 C08K5/00 C08L23/10

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols) $IPC \ 6 \ C08K$

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
outego.,		
Α	EP 0 369 658 A (SUMITOMO) 23 May 1990 see page 2, line 40 - line 45; claims 1-3; examples; table 1	1,4,5
Α ·	EP 0 417 319 A (MITSUBISHI) 20 March 1991 cited in the application see page 2, line 24 - line 35; claims 1,5; examples	1,4-7
Α	GB 1 104 665 A (ICI LTD.) see page 1, line 19 - line 20 see page 1, line 39 - line 53 see page 1, line 65 - line 70 see page 2, line 24 - line 26 see page 3, line 52 - line 61; claims 1,4,5,11,13,19,34; examples	1,4-6,13

X Further documents are listed in the continuation of box C.	Patent family members are listed in annex.		
 Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed 	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art. "&" document member of the same patent family		
Date of the actual completion of the international search	Date of mailing of the international search report		
20 April 1999	03/05/1999		
Name and mailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Riiswiik	Authorized officer		
Tel. (+31-70) 340-2040, Tx. 31 651 epo ni, Fax: (+31-70) 340-3016	Engel, S		

1

	ation) DOCUMENTS CONSIDERED TO BE RELEVANT	Relevant to claim No.
ategory *	Citation of document, with indication where appropriate, of the relevant passages	невечан по ставт по.
	EP 0 151 883 A (SUMITOMO) 21 August 1985 cited in the application see page 15, line 23 - page 16, line 2; claims 1,6-9; examples; table 2	1,4-6
		;

1

information on patent family members

Application No
PCT/EP 98/07215

	tent document in search report		Publication date		Patent family member(s)		Publication date	
EP	369658	A	23-05-1990	JP JP CA DE DE SG US	2135245 / 2762492 E 2001234 / 68928768 E 68928768 T 47424 / 5032645 / 5115027 /	B A,C D T A	24-05-1990 04-06-1998 16-05-1990 10-09-1998 14-01-1999 17-04-1998 16-07-1991 19-05-1992	·
EP	417319	Α	20-03-1991	JP JP JP DE DE US WO		A A D T A	03-09-1998 06-02-1991 23-01-1991 07-11-1996 06-03-1997 15-02-1994 04-10-1991	
GB	1104665	Α		BE DE FR NL	679547 / 1595842 / 1476249 / 6605058 /	A A	14-10-1966 14-05-1970 21-06-1967 17-10-1966	
EP	151883	A	21-08-1985	JP JP CA CA DE EP SG US	60139731 / 1255048 / 1254690 / 3471942 / 0152701 / 96994 /	B A A A G A	28-05-1993 26-06-1991 24-07-1985 30-05-1989 23-05-1989 14-07-1988 28-08-1985 12-05-1995 29-09-1987 05-11-1985	